



# SuperGlaze VOC

## Moisture Cure Urethane

### MATERIAL SAFETY DATA SHEET

Page 1 of 5  
Effective: August 01, 2000

#### SECTION 1 - PRODUCT IDENTIFICATION

**Common Name:** SuperGlaze VOC  
(As appears on label)

**Product Use/Class:** Industrial Sealer/Coating

**Manufacturer/Supplier:** Concrete Coatings Inc.  
PO Box 150071  
Ogden, UT 84415  
1-800-443-2871

**Prepared by:** Troy Harris, Technical Director

**Emergency:** Chemtrec 1-800-424-9300

Hazard Rating	Scale	
Toxicity	2	4 = Extreme
Flammability	3	3 = High
Reactivity	0	2 = Moderate
Special	0	1 = Slight
		0 = Insignificant

#### SECTION 2 – HAZARDOUS INGREDIENTS

(Occupational Exposure Limits)

(Vapor Pressure)

Hazardous Components Chemical & Common Names	CAS No.	MFG TLV	OSHA PEL	ACGIH TLV	mm Hg	Hg@Temp
<b>SuperGlaze VOC, Clear</b>						
*3-Isocyanatomethyl – 3, 5, 5 Trimethyl Cyclohexyl Isocyanate	4098-71-9		.005 ppm (SKIN)	.005 ppm (SKIN)	.0003	68°F (20°C)
*Dimethyl Benzene	1330-20-7		100 ppm (STEL-125 ppm)	100 ppm (STEL-125 ppm)	14.0	100°F(38°C)
Urethane Prepolymer			N/E	N/E		77°F (25°C)

\*Indicates toxic chemical(s) subject to the reporting requirement of section 313 of Title III and of 40 CFR 372. Information concerning non-hazardous ingredients is considered a Trade Secret.

#### SECTION 3 – PHYSICAL/CHEMICAL CHARACTERISTICS

**Boiling Range:** >280°F (138°C)

**Specific Gravity (Water=1):** 0.98

**Coating V.O.C.:** 340 g/l (2.8/gal)

**Vapor Density (Air=1):** N/A

**Solubility in Water:** Reacts with water

**Evaporation Rate  
(Butyl Acetate=1):** Slower than ether

**Appearance & Odor** Think liquid with strong aromatic odor

**PH:** N/D

**Viscosity** N/D

#### SECTION 4 – FIRE AND EXPLOSION DATA

**Flash Point:** 79°F (26°C)

**Method Used:** TCC

**Flammable Limits:** Lower: 1.0%  
(Based on n-Butyl Acetate) Upper: 7.1%

**Extinguishing Media:**

Dry chemical, foam, carbon dioxide. If water is used, use very large quantities of cold water. The reaction between water and hot isocyanate may be vigorous.

**Unusual Fire/Explosion:**

Water contamination will produce carbon dioxide. Do not reseal contaminated containers as pressure buildup may rupture them. Combustible.

**Special Firefighting Procedures:**

Wear NIOSH approved self-contained breathing apparatus in positive pressure mode with full-face piece. Boots, gloves (neoprene), goggles, and full protective clothing are also required. Excessive pressure or temperature may cause explosive rupture of containers.

---

**SECTION 5 – REACTIVITY DATA**

**Stability:**

Stable under normal conditions

**Conditions to avoid:**

Heat, high temperature, open flame, sparks, and moisture. Contact with incompatible materials in a closed system will cause liberation of carbon dioxide and buildup of pressure.

**Incompatible with (Materials to avoid):**

This product will react with any material containing active hydrogens, such as water, alcohol, ammonia, amines, alkalis and acids, the reaction with water is very slow under 50°C, but is accelerated at higher temperature and in the presence of alkalis, tertiary amines, and metal compounds. Some reactions can be violent. Material can react violently with strong oxidizing agents.

**Hazardous decomposition products:**

Carbon dioxide, carbon monoxide, nitrogen oxides, ammonia, trace amounts of hydrogen cyanide and unidentified organic compounds may be formed during combustion.

**Hazardous polymerization:**

Will not occur under normal conditions but under high temperatures in presence of alkalis, tertiary amines, and metal compounds will accelerate polymerization. Possible evolution of carbon dioxide gas may rupture closed containers.

---

**SECTION 6 HEALTH HAZARD DATA**

**Skin Contact:**

Some components used in this material when spilled on the skin may cause irritation, redness, swelling, or blistering. Repeated contact may cause irritation of the skin and an allergic skin reaction consisting of a hive-like rash on locations not even directly contacted by the liquid. Individuals who have developed a skin sensitization can develop these symptoms as a result of contact with very small amounts of liquid material or as a result of exposure to vapor.

**Eye Contact:**

Liquid, aerosols or vapors are severely irritating and can cause pain, tearing, reddening and swelling. The effects of liquid directly contacting the eye can lead to possible damage to the cornea and impairment of vision. The effects of high vapor concentration may vary from slight irritation with tearing and burning sensation to keratitis consisting of inflammation of the cornea and impairment of vision. Any level of contact should not be left untreated.

**Skin Absorption:**

Systemically toxic concentrations of this product will probably not be absorbed through human skin.

**Ingestion:**

Can result in irritating and corrosive action in the mouth, stomach tissue and digestive tract and gastroenteritis. Symptoms can include sore throat, headache, abdominal pain, nausea, vomiting and diarrhea. Pronounced gastroenteritis effects would probably occur on repeated ingestion.

**Inhalation:**

Isocyanate vapors or mist at concentrations above the TLV can irritate (burning sensation) the mucous membranes in the respiratory tract (nose, throat, lungs) causing runny nose, sore throat, coughing, chest discomfort, shortness of breath and reduced lung function (breathing obstruction). High vapor concentrations may cause central nervous system (CNS) depression as evidenced by giddiness, headache, dizziness, and nausea. Persons with a preexisting, non-specific bronchial hyperactivity can respond to concentrations below the TLV with similar symptoms as well as asthma attack. Exposure well above the TLV may lead to bronchitis, bronchial spasm and pulmonary edema (fluid in lungs). As a result of previous repeated overexposures or a single large dose, certain individuals may develop isocyanate sensitization (chemical asthma) which will cause them to react to a later exposure to isocyanate at levels well below the TLV. Similar to many non-specific asthmatic responses, there are reports that once sensitized an individual can experience these symptoms upon exposure to dust, cold air or other irritants. This increased lung sensitivity can persist for weeks and in severe cases for several years. Chronic overexposure to isocyanate has also been reported to cause lung damage (including decrease in lung function) which may be permanent. Sensitization can either be temporary or permanent.

**Health Hazards:**

**ACUTE:** Exposure may cause mucous membrane and respiratory tract irritation, tightness of chest, headache, shortness of breath, and a dry cough. At concentrations exceeding current occupational limits and for sensitized individuals at levels less than or greater than current occupational limits, asthma-like symptoms may occur. These symptoms may include coughing, wheezing, and shortness of breath. A hypersensitive pneumonitis may also occur if the person is sensitized. This syndrome is characterized by fever, nonproductive cough, wheezing, chills, and shortness of breath. Central nervous system (CNS) depression may also result. The effects of acute exposure may be delayed in onset up to 12-24 hours. **CHRONIC:** Repeated exposure above current occupational limits may cause an allergic sensitization of the respiratory tract. This is characterized by an asthma-like response upon re-exposure to the chemical. The symptoms may include coughing, wheezing, shortness of breath and chest tightness, and may be fatal. Central nervous system (CNS) impairment possibly leading to unconsciousness.

**Carcinogenicity:**

NTP: No            IARC Monographs: No            OSHA Regulated: No

**Medical conditions generally aggravated by exposure:** Cardiovascular disease, asthma or asthmatic bronchitis, emphysema, allergic disease, chronic respiratory disease, sinusitis, headache, dizziness.

**Emergency and First Aid:**

Immediately flush eyes with plenty of water, preferably lukewarm. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Have eyes examined and treated by medical personnel. **INHALATION:** Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is labored, give oxygen. Consult medical personnel. **SKIN CONTACT:** Wash material off the skin thoroughly with plenty of soap and water. If redness, itching, or a burning sensation develops, get medical attention. Wash contaminated clothing and decontaminate footwear before reuse. **INGESTION:** Do not induce vomiting. Immediately drink large quantities of water and refer person to medical personnel. Do not give anything by mouth to an unconscious person.

**SECTION 7 – SPILL OR LEAK PROCEDURES**

**Steps to be taken if material is released or spilled:**

Wear skin, eye, and respiratory protection during cleanup. Soak up material with absorbent and shovel into a chemical waste container. Cover container, but do not seal, and remove from work area. Prepare a decontamination solution of 2.0% liquid detergent and 3-8% concentrated ammonium hydroxide in water (5-10% sodium carbonate may be substituted for the ammonium hydroxide). Follow the precautions on the supplier's material safety data sheets. All operations should be performed by trained personnel familiar with the hazards of the chemicals used. Treat the spill area with the decontamination solution, using about 10 parts of solution for each part of the spill, and allow it to react for at least 15 minutes. Carbon dioxide will be evolved, leaving insoluble polyureas. Residues from spill cleanup, even when treated as described may continue to be regulated under provisions of RCRA and require storage and disposal as hazardous waste. For major spills, call CHEMTREC (Chemical Transportation Emergency Center) at 800-424-9300.

---

**Waste Disposal Method:**

Slowly stir the isocyanate waste into the decontamination solution described above. Let stand for 48 hours, allowing the evolved carbon dioxide to vent away, residues may still be subject to RCRA storage and disposal requirements. Dispose off in compliance with all relevant local, state, and federal laws and regulations regarding treatment.

**Precautions to be taken in Handling and Storing:**

Keep in cool, dry, ventilated storage area, in closed containers and out of direct sunlight. Keep liquid and vapors away from heat, sparks and flame, store in containers above ground and surrounded by dikes to contain spills or leaks. Sufficient heat or pressure may ignite or detonate even liquid product in the absence of sparks or open flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use until all vapors are gone. Vapors may accumulate and travel to ignition sources distant from the handling site; flash fire can result. Keep containers closed when not in use. Containers, even those that have been emptied, may contain explosive vapors. Do not cut, drill, grind, weld or perform similar operations on or near containers. Do not pressurize containers to empty them. Use explosion-proof lighting and equipment, non-sparking tools, clothes and shoes. Ground all structures, transfer containers, equipment to conform to the national electrical code. Use procedures that prevent static electrical sparks. Static electricity may accumulate and create a fire hazard.

**Other Precautions:**

Prevent skin and eye contact, observe TLV limitations. Avoid breathing vapors. Workers should shower and change to fresh clothing after each shift. A sensitized individual should not be exposed to the product that caused the sensitization. Air circulation and exhaustion of vapors must be maintained until the coatings have fully cured to insure that no potential fire, explosion or health hazard remains. Warning properties (irritation of the eyes, nose and throat or odor) are not adequate to prevent chronic overexposure from inhalation. This product can produce asthmatic sensitization upon either single inhalation exposure to a relatively high concentration or upon repeated inhalation exposure to lower concentrations. Exposure to vapors of heated product can be extremely dangerous. Employee education and training in safe handling of this material is required under OSHA hazard communication standard. Individuals with existing respiratory disease such as chronic bronchitis, emphysema, or asthma should not be exposed to the product. These individuals should be identified through baseline and annual evaluation and removed from further exposure. Medical examination should include medical history, vital capacity, and forced expiratory volume at one second.

---

**SECTION 8 – SAFE HANDLING AND STORAGE INFORMATION**

**Ventilation:**

The use of mechanical dilution ventilation is recommended whenever this product is used in a confined space, is heated above ambient temperatures, or is agitated. Use explosion-proof ventilation equipment. Use local exhaust ventilation to keep airborne concentrations below the TLV. Follow guidelines in the ACGIH publication 'Industrial Ventilation'. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination.

**Respiratory Protection:**

If airborne concentrations exceed or are expected to exceed the TLV, use MSHA/NIOSH approved positive pressure supplied air respirator with a full face piece or an air supplied hood. For emergencies, use a positive pressure self-contained breathing apparatus. Air purifying (cartridge type) respirators are not approved for protection against isocyanates.

**Protective Clothing:**

Gloves determined to be impervious under the conditions of use should be worn always when working with this product. Depending on conditions of use, additional protection may be required such as apron, arm covers, or full body suit. Wash contaminated clothing before re-wearing. Protective clothing should be selected and used in accordance with "Guidelines for the Selection of Chemical Protective Clothing" published by ACGIH.

**Eye Protection:**

Chemical tight goggles and full-face shield.

**Other Protective Equipment and Measures:**

Unhindered access to safety shower and eye wash stations. As a general hygienic practice, wash hands and face after use. Showers and cleaning of clothes are recommended. Follow all label instructions. Educate and train employees in safe use of product.



# SuperGlaze VOC

## Moisture Cure Urethane

### MATERIAL SAFETY DATA SHEET

Page 5 of 5  
Effective: August 01, 2000

---

## SECTION 9 – SHIPPING INFORMATION

---

### DOT Proper Shipping Name:

Paint, Class 3, UN 1263, PG III, Flammable Liquid.

### IATA Proper Shipping Name:

Paint, Class 3, UN 1263, PG III, Flammable Liquid.

### IMO Proper Shipping Name:

Paint, Class 3, UN 1263, PG III, Flammable Liquid.

### State Regulations:

#### California

As per requirements of the Safe Drinking Water & Toxic Enforcement Act of CA, USA 1985 (Proposition 65), the public is warned that materials used in this product may create an exposure to chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm. This warning required by Section 25249.6 of the California Health and Safety Code.

### TSCA (Toxic Substance Control Act):

All chemicals comprising this product are listed on the TSCA inventory.

**USERS RESPONSIBILITY & DISCLAIMER OF LIABILITY:** A bulletin such as this cannot be expected to cover all possible situations. As the user has the responsibility to provide a safe workplace, all aspects of an individual operation should be examined to determine if, or where precautions – in addition to those described herein are required. Although the information contained herein is based on data considered to be accurate, all materials present unknown health hazards, and should be used with caution and by properly trained personnel. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Any health hazard and safety information should be passed onto your customers or employees, as the case may be. Final suitability of the chemical for each circumstance is the sole responsibility of the end user. No representation or warranties either expressed or implied, of merchantability, fitness for a particular purpose, or any other nature are made hereunder with respect to the information contained herein, or the chemical to which the information refers. It is the sole responsibility of the end user to comply with all applicable federal, state and local laws and regulations. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed.